



South Coast Air Quality Management District

21865 Copley Drive, Diamond Bar, CA 91765-4178
(909) 396-2000 • www.aqmd.gov

January 08, 2010

Mr. Gerardo Rios
Chief, Permits Office
US EPA, Region IX- Air 3.
75 Hawthorne Blvd.
San Francisco, CA 94105

Dear Mr. Rios:

Disneyland Resort, (ID 800189, SIC code 7900) has proposed to revise their Title V permit by adding the following equipment in section D:

| Application No. | Equipment | Device no. | Process/System |
|-----------------|-----------------|------------|----------------|
| 504518 | Pressure Washer | D284 | 2 |
| 504519 | Pressure Washer | D285 | 2 |
| 504520 | Pressure Washer | D286 | 2 |
| 504521 | Pressure Washer | D287 | 2 |
| 504522 | Pressure Washer | D288 | 2 |

The following equipment will be removed from Section D:

| Application No. | Equipment | Device no. | Process/System |
|-----------------|-----------------|------------|----------------|
| 471089 | Pressure Washer | D227 | 2 |

This proposed revision is a "de minimis significant permit revision" to the Title V permit. Please review the attached draft Sections D. Questions concerning changes to the permit should be directed to Mr. Roy Olivares at (909) 396-2208.

Very truly yours,

Michael D. Mills

Michael D. Mills
Senior Manager
General Commercial & Energy Team
Engineering and Compliance

Attachments
CERTIFIED MAIL

Cleaning the air that we breathe...

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| System 1 : EMERGENCY | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DN, WITH TURBOCHARGER, 210 HP A/N: 478422 | D1 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11; D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DT, WITH TURBOCHARGER, 137 HP A/N: 478423 | D2 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DN, 210 HP A/N: 180124 | D3 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, E71.7, H23.6 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DT, WITH TURBOCHARGER, 290 HP A/N: 478424 | D4 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, D12.1, E71.4, E71.7, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, FORD, MODEL 4DEF4XR1601B, 52 HP A/N: 180129 | D5 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, E71.7, H23.6 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DT, WITH TURBOCHARGER, 137 HP A/N: 478425 | D7 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 64DTA, WITH AFTERCOOLER, TURBOCHARGER, 163 HP A/N: 478426 | D8 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 133DTA, WITH AFTERCOOLER, TURBOCHARGER, 368 HP A/N: 195818 | D10 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.2, C177.1, D12.1, E71.7, H23.6 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 6.4DTA, WITH AFTERCOOLER, TURBOCHARGER, 160 HP A/N: 478430 | D12 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3208TA, WITH AFTERCOOLER, TURBOCHARGER, 299 HP A/N: 478431 | D15 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, DETROIT DIESEL, MODEL 40-8.7LT, WITH TURBOCHARGER, 205 BHP A/N: 478432 | D95 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3508 DITA, WITH AFTERCOOLER, TURBOCHARGER, 1337 BHP A/N: 303611 | D98 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.3, C177.1, D12.1, E71.6, H23.6 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, JOHN DEERE, MODEL 6059T, WITH A TURBOCHARGER, 166 BHP A/N: 478433 | D99 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, GENERAC 7.4GN, MODEL CG070, WITH CATALYTIC REDUCTION, 116 HP A/N: 334912 | D101 | | NOX: PROCESS UNIT** | NOX: 37.9 LBS/MMSCF NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-5-2003 RULE 2012,5-6-2005] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, H23.12 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344925 | D115 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995] | C1.1, D12.1, H23.12, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|----------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | <p><i>RULE 2012,4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p> | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344926 | D116 | | NOX: PROCESS UNIT** | <p>CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 <i>RULE 2012,4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999]</p> | C1.1, D12.1, H23.12, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|---------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344927 | D117 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344928 | D118 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|-------------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3408SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 460 BHP A/N: 344929 | D119 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] | C1.1, D12.1, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3306SITA, NATURAL GAS, RICH BURN, WITH TURBOCHARGER AND AFTERCOOLER, WITH CATALYTIC REDUCTION, 194 BHP A/N: 344913 | D120 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 | C1.1, D12.1, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3304SINA, NATURAL GAS, WITH CATALYTIC REDUCTION, 95 BHP A/N: 344914 | D121 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|---------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3516SITA, NATURAL GAS, LEAN BURN, WITH TURBOCHARGER AND AFTERCOOLER, 1482 BHP A/N: 344899 | D122 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 1.5-GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344933 | D123 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|-------------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344934 | D124 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344935 | D125 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 | C1.1, D12.1, H23.12, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|----------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | <p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9-1999] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]</p> | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344936 | D126 | | NOX: PROCESS UNIT** | <p>CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 12-7-1995]</p> <p><i>RULE 2012, 4-9-1999</i> ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 10-15-1993; RULE 2005, 4-9-1999] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996]</p> | C1.1, D12.1, H23.12, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|----------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344937 | D127 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 405,2-7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344938 | D128 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] | C1.1, D12.1, H23.12, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|-------------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CATERPILLAR, MODEL G3406SITA, NATURAL GAS, WITH CATALYTIC REDUCTION, 367 BHP A/N: 344939 | D129 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9- 1999] ; PM: (9) [RULE 404,2- 7-1986] ROG: 1 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY-FIRE, GASOLINE, FORD, MODEL LSG-875R-6003-C, WITH CATALYTIC REDUCTION, 193 HP A/N: 359091 | D131 | | NOX: PROCESS UNIT** | CO: 0.6 GRAM/BHP-HR GASOLINE (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 102 LBS/1000 GAL GASOLINE (1) [RULE 2012,12- 7-1995;RULE 2012,4-9-1999] | C1.1, D12.1, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | NOX: 0.15 GRAM/BHP-HR GASOLINE (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 0.15 GRAM/BHP-HR GASOLINE (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 7.5 DTA, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 184 BHP A/N: 362182 | D133 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] ; NOX: 264 LBS/1000 GAL.DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,10-15- 1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5- 10-1996] ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] | C1.1, D12.1, E71.6, E202.2, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, CUMMINS, MODEL 800 GTA 500 G3, NATURAL GAS, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 1334 BHP A/N: 360419 | D134 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, E202.3, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, GENERAC, MODEL 7.5 DTA, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 184 BHP A/N: 367064 | D146 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 264 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,4-9-1999] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,10-15-1993;RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, D12.1, E71.6, E202.2, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements
** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3303 ATACC, WITH AFTERCOOLER, TURBOCHARGER, 377 BHP A/N: 378803 | D149 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] ; NOX: 302 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995 RULE 2012,4-9-1999] ; NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5- 10-1996;RULE 1303(a)(1)- BACT,10-20-2000] ; PM: (9) [RULE 404,2-7-1986] PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] ; ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996 RULE 1303(a)(1)-BACT,10-20- 2000] | C1.1, C1.11, D12.1, E71.1, E71.4, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section E and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, PARADISE PIER HOTEL, DIESEL FUEL, CUMMINS, MODEL N-855-F, 6 CYLINDERS, FOUR CYCLE, NATURALLY ASPIRATED, SERIAL NO. 1815303, 240 HP A/N: 311603 | D152 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.22, D12.1, H23.6 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, PARADISE PIER HOTEL, DIESEL FUEL, CATERPILLAR, MODEL 3508DI, 8 CYLINDERS, INTERCOOLED, SERIAL NO. 28Z00641, WITH TURBOCHARGER, 712 HP A/N: 478427 | D153 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.20, C177.1, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 4BT3.9-G4, 4 CYLINDERS, SERIAL NO. 45901859, WITH TURBOCHARGER, 102 HP A/N: 363159 | D159 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.8, D12.1, E71.6, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 478428 | D160 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.11, C177.1, D12.1, E71.4, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 241137 | D162 | | NOX: PROCESS UNIT** | NOX: 2.9 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10- 1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16- 2001] PM: (9) [RULE 404,2-7-1986] ; ROG: 0.11 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5- 10-1996] | C177.1, D12.1, E71.6, H23.6, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, CUMMINS, MODEL 6CT8.3G, 6 CYLINDERS, FOUR CYCLE, WITH TURBOCHARGER, 207 HP A/N: 241138 | D163 | | NOX: PROCESS UNIT** | NOX: 2.9 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10- 1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16- 2001] | C177.1, D12.1, E71.6, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | PM: (9) [RULE 404,2-7-1986] ; ROG: 0.11 LBS/HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DISNEYLAND HOTEL, DIESEL FUEL, CLARKE GM DIESEL INC, MODEL MD-4-1226, 4 CYLINDERS, SERIAL NO. 47463, 73 HP A/N: 241139 | D164 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986] | C1.8, C1.22, D12.1, H23.6, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DISNEYLAND HOTEL, DIESEL FUEL, ALLIS- CHALMERS, MODEL 649, 6 CYLINDERS, FOUR CYCLE, SERIAL NO. K820640605, 73 HP A/N: 478429 | D168 | | NOX: PROCESS UNIT** | NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995;RULE 2012,3-16-2001] ; PM: (9) [RULE 404,2-7-1986] | C1.1, C1.20, D12.1, E71.6, E116.1, H23.6, H23.11, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, JOHN DEERE, MODEL 6081A, WITH AFTERCOOLER, TURBOCHARGER, 250 BHP A/N: 397419 | D169 | | NOX: PROCESS UNIT** | CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996] ; NOX: 304 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] | C1.1, C1.11, D12.1, E71.1, E71.4, H23.6, K67.4 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | <p>NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-9-1999;RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p> <p>ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p> | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY FIRE, DIESEL FUEL, CUMMINS, MODEL 6BTA5.9F1, PARADISE PIER HOTEL, WITH AFTERCOOLER, TURBOCHARGER, 182 BHP A/N: 408907 | D172 | | NOX: PROCESS UNIT** | <p>CO: 8.5 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995;RULE 2012,3-16-2001]</p> <p>NOX: 6.9 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-9-1999;RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; PM10: 0.38 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p> <p>ROG: 1 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; SOX: 15 PPMM DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996]</p> | C1.1, C1.22, D12.1, H23.6, K67.4, K67.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3412STIA/450KW, SERIAL NO. 7DM, JOHNSON MATTHEY-MODEL QXC-30-08-NSCR, MODEL EPC-100-CONTROLLER, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 622 BHP A/N: 412302 | D173 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,3-16-2001] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996] | C1.1, C1.11, D12.1, E71.1, E202.3, H23.12, K67.4 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CUMMINS, MODEL-GTA14 GS/GC 280 KW, WITH NSCR-MIRATECH, MODEL MCS-22Y1515-08-C2, CONTROLLER-MODEL MEC-2001-1LP, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 431 BHP A/N: 419597 | D174 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 | C1.1, C1.11, D12.1, E71.3, E202.3, H23.12, K67.13 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | <p><i>RULE 2012, 3-16-2001</i> ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005, 4-9-1999; RULE 2005, 4-20-2001] ; PM: (9) [RULE 404, 2-7-1986]</p> <p>ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002]</p> | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, PERKINS, MODEL 1004-40T, WITH TURBOCHARGER, 95.2 BHP A/N: 425385 | D175 | | NOX: PROCESS UNIT** | <p>CO: 3.7 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002] ; NOX: 469 LBS/1000 GAL DIESEL (1) [RULE 2012, 12-7-1995 <i>RULE 2012, 3-16-2001</i> ; NOX + ROG: 5.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 4-20-2001]</p> <p>PM: 0.3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002] ; PM: (9) [RULE 404, 2-7-1986]</p> | C1.1, C1.11, D12.1, E71.4, H23.6, K67.14 |

* (1)(1A)(1B) Denotes RECLAIM emission factor.

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g., NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3406SITA (250-KW), WITH NSCR, JOHNSON MATTHEY, QXC20, A/E, WOODWARD, MODEL GECO, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 367 BHP A/N: 431660 | D176 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-5-2003 RULE 2012,5-6-2005] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] | C1.1, C1.11, D12.1, E71.5, E202.3, H23.12, K67.14 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, FORD, MODEL WSG-1068, WITH NSCR, MINE-X, MODEL DC47, NEUTRONIC, MARK V, A/F CONTROLLER, WITH CATALYTIC REDUCTION, TURBOCHARGER, 176 BHP A/N: 436095 | D178 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] ; NOX: 2192.45 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995] | C1.1, D12.1, E202.3, H23.12, K67.14 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,4-20-2001] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445773 | D179 | | NOX: PROCESS UNIT** | CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5-2003 RULE 2012,1-7-2005] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20-2001] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] | C1.1, D12.1, E71.4, E116.1, H23.6, K67.16 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g., NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445774 | D180 | | NOX: PROCESS UNIT** | CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5-2003] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20-2001] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] | C1.1, D12.1, E71.4, E116.1, H23.6, K67.16 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL G3456 DITA AA, WITH AFTERCOOLER, TURBOCHARGER, 685 BHP A/N: 445775 | D181 | | NOX: PROCESS UNIT** | CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 221 LBS/1000 GAL DIESEL (1) [RULE 2012,12-5-2003] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 2005,4-20-2001] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] | C1.1, D12.1, E71.4, E116.1, H23.6, K67.16 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
- (2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, FORD, MODEL ESG-642, WITH NSCR, MODEL L102, WITH AIR FUEL RATIO CONTROLLER, WITH CATALYTIC REDUCTION, 67 BHP A/N: 444735 | D182 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 437 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 RULE 2012,3-16-2001] ; NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; PM: (9) [RULE 404,2-7-1986] ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] | C1.1, D12.1, E71.4, E71.5, H23.12, K67.14 |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL 3306ATACC, WITH AFTERCOOLER, TURBOCHARGER, 377 BHP A/N: 445546 | D183 | | NOX: PROCESS UNIT** | CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)- BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] ; NOX: 209 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7- 1995 | C1.1, D12.1, E71.4, E116.1, H23.6, K67.16 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | <p><i>RULE 2012, 3-16-2001] ; NOX + ROG: 4.8 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002;RULE 2005,4-20-2001</i></p> <p><i>RULE 2005,5-6-2005] ; PM: 0.15 GRAM/BHP-HR DIESEL (5) [RULE 1470,6-1-2007] ; PM: (9) [RULE 404,2-7-1986]</i></p> <p>PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002]</p> | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, DIESEL FUEL, CATERPILLAR, MODEL C-9 DITA, LOCATED AT NEMO SITE, WITH AFTERCOOLER, TURBOCHARGER, 398 BHP A/N: 459428 | D223 | | NOX: PROCESS UNIT** | <p>CO: 2.6 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 136 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005]</p> <p>NOX + ROG: 3 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002;RULE 2005,5-6-2005] ; PM: 0.15 GRAM/BHP-HR.DIESEL (5) [RULE 1470,6-1-2007]</p> | C1.1, C1.11, D12.1, E71.4, E116.1, H23.6, K67.16 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | PM: (9) [RULE 404,2-7-1986] ; PM10: 0.15 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)- BACT,5-10-1996;RULE 1303(a),12-6-2002] | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, CATERPILLAR, MODEL G3046 SITA, WITH NSCR,JOHNSON MATHEY, MODEL QXE.10-8, A/F, GILL MODEL 120, WITH CATALYTIC REDUCTION, AFTERCOOLER, TURBOCHARGER, 367 BHP A/N: 478405 | D259 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 413 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,5-6-2005] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)- BACT,5-10-1996 RULE 1303(a),12-6-2002] | C1.1, C1.11, D12.1, E71.5, E116.1, E202.3, H23.12, K67.14 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| INTERNAL COMBUSTION ENGINE, EMERGENCY POWER, NATURAL GAS, GENERAL MOTORS, MODEL VORTEC 8.1 L POWERTRAIN, WITH NSCR, CLEAN AIR, MODEL CQD0950BCCN40 WITH AIR/FUEL RATIO CONTROLLER, WITH CATALYTIC REDUCTION, TURBOCHARGER, 195 BHP A/N: 499582 | D276 | | NOX: PROCESS UNIT** | CO: 2 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] ; NOX: 390 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] NOX: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 2005,5-6-2005] ; PM: (9) [RULE 404,2-7-1986] ; ROG: 1.5 GRAM/BHP-HR NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996 RULE 1303(a),12-6-2002] | C1.1, C1.11, D12.1, E71.5, E202.3, K67.14 |
| System 2 : NON - EMERGENCY | | | | | |
| INTERNAL COMBUSTION ENGINE, NON-EMERGENCY, DIESEL FUEL, JOHN DEERE, MODEL 4045TF275, ON-SITE PORTABLE DRIVING A WOOD CHIPPER, WITH TURBOCHARGER, 115 BHP A/N: 432411 | D177 | | NOX: PROCESS UNIT** | CO: 3.7 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996] ; NOX: 188 LBS/1000 GAL DIESEL (1) [RULE 2012,12-7-1995] | C1.12, D12.1, D323.1, K67.15 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor (2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit (4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit (6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit (8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|-----------------------------|
| Process 1 : INTERNAL COMBUSTION, INDUSTRIAL | | | | | |
| | | | | NOX + ROG: 4.9 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 2005,4-20-2001] ; PM: 0.22 GRAM/BHP-HR DIESEL (4) [RULE 1303(a)-BACT,5-10-1996] PM: (9) [RULE 404,2-7-1986] | |
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, EAST UNIT # 2, NATURAL GAS, SUPERIOR, MODEL LND145P, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 12.57 MMBTU/HR WITH A/N: 370698 BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER | D16 | | NOX: LARGE SOURCE** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 30 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995 RULE 2012,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | D12.3, D12.4, H23.4, H23.12 |
| BOILER, WEST UNIT # 2, NATURAL GAS, SUPERIOR, MODEL LND145S, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 9.95 MMBTU/HR WITH A/N: 405301 | D17 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 47.75 LBS/MMSCF NATURAL GAS (1) [RULE 2012,12-7-1995 | D12.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor.

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|-----------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER | | | | RULE 2012, 4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] | |
| BOILER, EAST UNIT # 1, NATURAL GAS, SUPERIOR, MODEL LND145P, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 12.57 MMBTU/HR WITH A/N: 370699 | D18 | | NOX: LARGE SOURCE** | CO: 2000 PPMV (5A) [RULE 407, 4-2-1982] ; CO: 400 PPMV (5) [RULE 1146, 11-17-2000] ; NOX: 30 PPMV NATURAL GAS (3) [RULE 2012, 12-7-1995] RULE 2012, 4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] | D12.3, D12.4, H23.4, H23.12 |
| BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER | | | | | |
| BOILER, WEST UNIT # 1, NATURAL GAS, SUPERIOR, MODEL LND145S, WITH FLUE GAS RECIRCULATION, OXYGEN CONTENT CONTROL, 9.95 MMBTU/HR WITH A/N: 405302 | D19 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407, 4-2-1982] ; CO: 400 PPMV (5) [RULE 1146, 11-17-2000] ; NOX: 47.75 LBS/MMSCF NATURAL GAS (1) [RULE 2012, 12-7-1995] RULE 2012, 4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409, 8-7-1981] | D12.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, INDUSTRIAL COMBUSTION, MODEL LNDG105, WITH LOW NOX BURNER | | | | | |
| BOILER, B1, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360389 | D135 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 400 PPMV (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | E202.4, H23.4, H23.12 |
| BURNER, NATURAL GAS, ALZETA, MODEL CSB84 | | | | | |
| BOILER, B2, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360386 | D137 | | NOX: PROCESS UNIT** | CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17- 2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] | E202.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, NATURAL GAS, ALZETA, MODEL CSB84 | | | | CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981] | |
| BOILER, B3, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360387 | D138 | | NOX: PROCESS UNIT** | CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17-2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] | E202.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS,etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, NATURAL GAS, ALZETA, MODEL CSB84 | | | | NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981] | |
| BOILER, B4, NATURAL GAS, CLEAVER BROOKS, MODEL FLX, WITH LOW NOX BURNER, 8.5 MMBTU/HR WITH A/N: 360388 | D139 | | NOX: PROCESS UNIT** | CO: 400 PPMV NATURAL GAS (5A) [RULE 1146,11-17-2000] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,10-20-2000] CO: 2000 PPMV NATURAL GAS (5) [RULE 407,4-2-1982] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,12-7-1995;RULE 2012,3-16-2001] NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,4-9-1999] ; PM: 0.1 GRAINS/SCF NATURAL GAS (5) [RULE 409,8-7-1981] | E202.4, H23.4, H23.12 |
| BURNER, NATURAL GAS, ALZETA, MODEL CSB84 | | | | | |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

(10) See Section J for NESHAP/MACT requirements

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|-------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000 | | | | CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | |
| BOILER, PARADISE PIER HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 3, 5 MMBTU/HR WITH A/N: 459432 | D209 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | D12.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

(10) See Section J for NESHAP/MACT requirements

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000 | | | | CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | |
| BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 2, 5 MMBTU/HR WITH A/N: 473757 | D215 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | C1.13, D12.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

(10) See Section J for NESHAP/MACT requirements.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000 | | | | CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | |
| BOILER, DISNEYLAND HOTEL, NATURAL GAS, CAMUS HYDRONICS LIMITED, MODEL 5001-DFX, NO. 5, 5 MMBTU/HR WITH A/N: 473762 | D221 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)-BACT,5-10-1996;RULE 1303(a),12-6-2002] CO: 400 PPMV NATURAL GAS (5) [RULE 1146,11-17-2000] ; NOX: 12 PPMV NATURAL GAS (3) [RULE 2012,5-6-2005] ; NOX: 12 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | C1.13, D12.4, H23.4, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BURNER, BEKAERT COMBUSTION TECHNOLOGY, MODEL DF-5000 | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, LANDA, MODEL VHW 3-700, 0.21 MMBTU/HR A/N: 471806 | D224 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, STEAM X, MODEL DELCO, 0.28 MMBTU/HR A/N: 471807 | D225 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, STEAM X, MODEL VANGUARD, 0.28 MMBTU/HR A/N: 471808 | D226 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 407,4-2-1982] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, A&M EQUIPMENT SERVICE, MODEL AMHGD-2003, NO. 2, 0.21 MMBTU/HR A/N: 471810 | D228 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
 (3) Denotes RECLAIM concentration limit
 (5)(5A)(5B) Denotes command and control emission limit
 (7) Denotes NSR applicability limit
 (9) See App B for Emission Limits
 (2)(2A)(2B) Denotes RECLAIM emission rate
 (4) Denotes BACT emission limit
 (6) Denotes air toxic control rule limit
 (8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
 (10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 1, 0.3 MMBTU/HR A/N: 471811 | D229 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 2, 0.3 MMBTU/HR A/N: 471812 | D230 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 1, 0.3 MMBTU/HR A/N: 471813 | D231 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 2, 0.3 MMBTU/HR A/N: 471814 | D232 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 3, 0.3 MMBTU/HR A/N: 471816 | D233 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 4, 0.3 MMBTU/HR A/N: 471817 | D234 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 5, 0.3 MMBTU/HR A/N: 471818 | D235 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 6, 0.3 MMBTU/HR A/N: 471820 | D236 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 7, 0.3 MMBTU/HR A/N: 471821 | D237 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 8, 0.3 MMBTU/HR A/N: 471822 | D238 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 9, 0.3 MMBTU/HR A/N: 471823 | D239 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 10, 0.3 MMBTU/HR A/N: 471824 | D240 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
- (2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 1, 0.56 MMBTU/HR A/N: 471825 | D241 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 2, 0.56 MMBTU/HR A/N: 471826 | D242 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 3, 0.56 MMBTU/HR A/N: 471827 | D243 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.17, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 4, 0.56 MMBTU/HR A/N: 471829 | D244 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.17, D12.8, K67.24 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
- (2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 6, 0.56 MMBTU/HR A/N: 471831 | D246 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 8, 0.56 MMBTU/HR A/N: 471834 | D248 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.17, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 281, NO. 9, 0.56 MMBTU/HR A/N: 471835 | D249 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 1, 0.56 MMBTU/HR A/N: 471836 | D250 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 3, 0.56 MMBTU/HR A/N: 471839 | D252 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.17, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, WALTERS, MODEL 247, NO. 4, 0.56 MMBTU/HR A/N: 471840 | D253 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 11, 0.3 MMBTU/HR A/N: 478418 | D255 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.18, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 12, 0.3 MMBTU/HR A/N: 478419 | D256 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.18, D12.8, K67.24 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|---|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO. 13, 0.3 MMBTU/HR A/N: 478420 | D257 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.18, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 216, NO.14, 0.3 MMBTU/HR A/N: 478421 | D258 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.18, D12.8, K67.24 |
| HEATER, CPI, NO. 1, NATURAL GAS, FULTON, MODEL FT0400-C, WITH LOW NOX BURNER, 5.128 MMBTU/HR A/N: 478416 | D260 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] CO: 400 PPMV (5) [RULE 1146,11-17-2000;RULE 1146,9-5-2008] ; NOX: 24.57 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] NOX: 20 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986] | C1.19, C1.21, D12.4, D29.1, E202.4, H23.9, H23.12 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|---|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| HEATER, CPI, NO. 2, NATURAL GAS, FULTON, MODEL FT0400-C, WITH LOW NOX BURNER, 5.128 MMBTU/HR A/N: 478417 | D261 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; CO: 50 PPMV NATURAL GAS (4) [RULE 1303(a)(1)-BACT,5-10-1996;RULE 1303(a)(1)-BACT,12-6-2002] CO: 400 PPMV (5) [RULE 1146,11-17-2000;RULE 1146,9-5-2008] ; NOX: 24.57 LBS/MMSCF NATURAL GAS (1) [RULE 2012,5-6-2005] NOX: 20 PPMV NATURAL GAS (4) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] ; PM: (9) [RULE 404,2-7-1986] | C1.19, C1.21, D12.4, D29.1, E202.4, H23.9, H23.12 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 3, 0.3 MMBTU/HR A/N: 487371 | D262 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 4, 0.3 MMBTU/HR A/N: 487373 | D263 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 5, 0.3 MMBTU/HR A/N: 487374 | D264 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 7205, NO. 6, 0.3 MMBTU/HR A/N: 487375 | D265 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.14, C1.16, D12.8, K67.24 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3E209, NO. 1, 0.16 MMBTU/HR A/N: 498054 | D266 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3E209, NO. 2, 0.16 MMBTU/HR A/N: 498055 | D267 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3E209, NO. 3, 0.16 MMBTU/HR A/N: 498056 | D268 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3E209, NO. 4, 0.16 MMBTU/HR A/N: 498057 | D269 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3VE51, NO. 1, 0.175 MMBTU/HR A/N: 498058 | D270 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 409,8-7-1981] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3VE51, NO. 2, 0.175 MMBTU/HR A/N: 498059 | D271 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|--------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3VE52, NO. 1, 0.219 MMBTU/HR A/N: 498060 | D272 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3VE52, NO. 2, 0.219 MMBTU/HR A/N: 498061 | D273 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| HEATER, SPACE HEATER TYPE, PORTABLE, DIESEL FUEL, DAYTON, MODEL 3VE52, NO. 2, 0.219 MMBTU/HR A/N: 498061 | D274 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 409,8-7-1981] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.23, D12.8, K67.22 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL HOT2-1100, NO. 1, 0.16 MMBTU/HR A/N: 499580 | D275 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2005,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 407,4-2-1982] | B59.2, C1.24, D12.8, K67.22 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|--|------------------------------------|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 21X4, NO. 1, 0.3 MMBTU/HR A/N: | D284 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.26, D12.8, K67.23 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 21X4, NO. 2, 0.3 MMBTU/HR A/N: | D285 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.26, D12.8, K67.23 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 21X4, NO. 3, 0.3 MMBTU/HR A/N: | D286 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.26, D12.8, K67.23 |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, ALKOTA, MODEL 21X4, NO. 4, 0.3 MMBTU/HR A/N: | D287 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.26, D12.8, K67.23 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|---|
| Process 2 : EXTERNAL COMBUSTION, BOILERS, INDUSTRIAL | | | | | |
| BOILER, PRESSURE WASHER TYPE, PORTABLE, DIESEL FUEL, AM CLEANING EQUIPMENT, MODEL AM-HGD-2403, 0.21 MMBTU/HR A/N: | D288 | | NOX: PROCESS UNIT** | CO: 2000 PPMV (5A) [RULE 407,4-2-1982] ; NOX: 19 LBS/1000 GAL DIESEL (1) [RULE 2012,5-6-2005] ; PM: 0.1 GRAINS/SCF (5) [RULE 409,8-7-1981] | B59.2, C1.16, C1.26, D12.8, K67.23 |
| Process 3 : ORGANIC SOLVENT SURFACE COATING | | | | | |
| SPRAY COATING OPERATION, WATER WASH TYPE, WITH SPRAY BOOTH A/N: 12162X | D20 | | | PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008] | D322.2, H23.2, K67.3 |
| SPRAY COATING OPERATION, FLOOR TYPE, WITH 24 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 214087 | D21 | | | PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008] | A63.1, B27.4, C6.1, D12.2, D322.1, E175.1, H23.2, K67.2 |
| SPRAY COATING OPERATION, FLOOR TYPE, WITH 21 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 214086 | D22 | | | PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9-2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7-2003 RULE 1171,2-1-2008] | A63.1, B27.4, C6.1, D12.2, D322.1, E175.1, H23.2, K67.2 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|--|
| Process 3 : ORGANIC SOLVENT SURFACE COATING | | | | | |
| SPRAY COATING OPERATION, AUTOMOTIVE TYPE, WITH 22 EXHAUST FILTERS, EACH 20" X 25" X 2", WITH SPRAY BOOTH A/N: 19482X | D24 | | | PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9- 2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1171,11-7- 2003 RULE 1171,2-1-2008] | C6.1, D12.2, D322.1, E175.1, H23.2, K67.2 |
| SPRAY COATING OPERATION, SOLVENT, DISNEYLAND HOTEL, AUTOMOTIVE TYPE, WITH 44 EXHAUST FILTERS, EACH 20" X 25" X 1.5", WITH SPRAY BOOTH A/N: 241140 | D165 | | | PM: (9) [RULE 404,2-7-1986] ; ROG: (9) [RULE 1107,11-9- 2001;RULE 1107,1-6-2006;RULE 1136,6-14-1996;RULE 1145,2-14- 1997 RULE 1145,12-3-2004;RULE 1171,11-7-2003;RULE 1171,2- 1-2008] | B27.4, C1.9, C1.10, C6.1, D12.2, D322.1, E175.2, H23.2, K67.2, K67.8 |
| Process 4 : PETROLEUM MARKETING, CONSUMER FLEET FUELING | | | | | |
| System 1 : FUEL STORAGE AND DISPENSING SYSTEMS | | | | | |
| STORAGE TANK, UNDERGROUND, GASOLINE, NOT METHANOL COMPATIBLE, WITH OPW (VR-102-E), 10000 GALS A/N: | D36 | | | | D330.1, E193.1, J373.1, K67.20 |
| STORAGE TANK, UNDERGROUND, GASOLINE, NOT METHANOL COMPATIBLE, WITH OPW (VR-102-E), 10000 GALS A/N: | D40 | | | | D330.1, E193.1, J373.1, K67.20 |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
(2)(2A)(2B) Denotes RECLAIM emission rate
(3) Denotes RECLAIM concentration limit
(4) Denotes BACT emission limit
(5)(5A)(5B) Denotes command and control emission limit
(6) Denotes air toxic control rule limit
(7) Denotes NSR applicability limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(9) See App B for Emission Limits
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---------------------------------|--|
| Process 4 : PETROLEUM MARKETING, CONSUMER FLEET FUELING | | | | | |
| FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, GASOLINE, WITH BALANCE RETRACTOR (G-70-52-AM), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: | D88 | | | | D330.1, E193.2, J110.1, J373.1, K67.20 |
| FUEL DISPENSING NOZZLE, BALANCE TYPE PHASE II CONTROL, GASOLINE, WITH BALANCE RETRACTOR (G-70-52-AM), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: | D89 | | | | D330.1, E193.1, E193.2, J110.1, J373.1 |
| FUEL DISPENSING NOZZLE, VACUUM ASSIST PHASE II CONTROL, GASOLINE, WITH HEALY PHASE II EVR NOT INCLUDING ISD (VR0201-G), WITH PHASE II VAPOR RECOVERY SYSTEM A/N: | D90 | | | | D330.1, E193.1, E193.2, J110.1, J373.1, K67.19 |
| DISPENSE MOBILE FUELER, GASOLINE, FRANZEN-HILL (G-70-193), WITH TWO HEALY 100 JET PUMPS, 400 GALS; WIDTH: 3 FT 8 IN; HEIGHT: 3 FT 10 IN; LENGTH: 7 FT 1 IN A/N: 367066 | D147 | | | | C1.6, C1.7, E71.2, J110.1, J397.1, K67.6 |
| FUEL DISPENSING NOZZLE, GASOLINE, EQUIPPED WITH PHASE II VAPOR RECOVERY, HEALY, MODEL 400 ORVR A/N: 367066 | D148 | | | | |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit (e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|---|--------|--------------|---|---|---|
| Process 5 : FABRICATED METALS | | | | | |
| System 1 : | | | | | |
| ABRASIVE BLASTING, OPEN, SAND WITH A/N: 193050 ABRASIVE BLASTING NOZZLE, DIAMETER: 0.375 IN | D44 | | | PM: (9) [RULE 1140,2-1-1980;RULE 1140,8-2-1985;RULE 405,2-7-1986] | D323.1, K67.5 |
| ABRASIVE BLASTING, ROOM, SAND, BAGHOUSE SERVICES, WITH 3000 LB POT, WIDTH: 15 FT 8 IN; HEIGHT: 15 FT 11 IN; LENGTH: 28 FT WITH A/N: 385807 ABRASIVE BLASTING NOZZLE, 2, MAXIMUM WORKING PRESSURE OF 120 PSI, DIAMETER: 0.625 IN | D156 | C158 | | PM: (9) [RULE 404,2-7-1986] | B27.2, K67.11 |
| BAGHOUSE, UNITED AIR SPECIALIST, MODEL SBD24-3, PULSE JET CLEANING, SERIAL NO. 60042645, 7440 SQ.FT.; 24 CARTRIDGE A/N: 385808 | C158 | D156 | | PM: (9) [RULE 404,2-7-1986] | C6.2, D12.2, D322.3, D381.1, E102.1, K67.10 |
| ABRASIVE BLASTING, CARBON DIOXIDE (DRY ICE), COLDJET, MODEL 2000, WITH 40 POUND CAPACITY HOPPER WITH A/N: 404957 ABRASIVE BLASTING NOZZLE, 1, WITH A MAX. THROAT AREA OF 0.068 IN ² , 140 PSIA | D170 | | | PM: (9) [RULE 1140,2-1-1980;RULE 1140,8-2-1985;RULE 405,2-7-1986] | B59.1, D381.1, H23.5, K67.11 |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|--|-----------------------|
| Process 7 : FABRICATED METALS, MACHINING OPERATIONS | | | | | |
| System 1 : | | | | | |
| PLASMA ARC CUTTER, DUAL CARRIAGE TYPE, WITH A FOUR TORCH CAPACITY A/N: 243063 | D48 | C49 | | PM: (9) [RULE 405,2-7-1986] | D323.1 |
| ELECTROSTATIC PRECIPITATOR, TEPCO TRION, MODEL T5200, WITH A-3 H.P. BLOWER A/N: 249015 | C49 | D48 | | PM: (9) [RULE 404,2-7-1986] | D323.1, E202.1 |
| Process 8 : SMOKE EFFECTS | | | | | |
| System 1 : | | | | | |
| FILTER, HEPA, FARR A/N: 288923 | C96 | | | PM: (9) [RULE 404,2-7-1986] | D322.1, D323.1, K67.2 |
| Process 9 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES | | | | | |
| System 1 : | | | | | |
| RULE 219 EXEMPT EQUIPMENT, AIR CONDITIONING UNITS, COMFORT A/C | E102 | | | | H23.3 |
| RULE 219 EXEMPT EQUIPMENT, PRINTING EQUIPMENT, WITH RELATED COATING, LAMINATING AND DRYING EQUIPMENT | E104 | | | ROG: (9) [RULE 1130.1,12-13-1996;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | |

* (1)(1A)(1B) Denotes RECLAIM emission factor

(3) Denotes RECLAIM concentration limit

(5)(5A)(5B) Denotes command and control emission limit

(7) Denotes NSR applicability limit

(9) See App B for Emission Limits

(2)(2A)(2B) Denotes RECLAIM emission rate

(4) Denotes BACT emission limit

(6) Denotes air toxic control rule limit

(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)

(10) See Section J for NESHAP/MACT requirements

*** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

| Equipment | ID No. | Connected To | RECLAIM Source Type/ Monitoring Unit | Emissions * And Requirements | Conditions |
|--|--------|--------------|---|---|------------|
| Process 9 : R-219 EXEMPT EQUIPMENT SUBJECT TO SOURCE SPECIFIC RULES | | | | | |
| RULE 219 EXEMPT EQUIPMENT, CLEANING EQUIPMENT, SMALL, UNHEATED, NON-CONVEYORIZED | E105 | | | ROG: (9) [RULE 1171,11-7-2003;RULE 1171,2-1-2008] | H23.1 |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, PORTABLE, ARCHITECTURAL COATINGS | E107 | | | ROG: (9) [RULE 1113,11-8-1996;RULE 1113,7-13-2007;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | K67.1 |
| RULE 219 EXEMPT EQUIPMENT, HAND LAY, BRUSH AND ROLL UP RESIN OPERATIONS | E108 | | | ROG: (9) [RULE 1162,11-17-2000;RULE 1162,7-8-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS | E111 | | | ROG: (9) [RULE 1106.1,2-12-1999;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | |
| RULE 219 EXEMPT EQUIPMENT, LAMINATING EQUIPMENT, LOW USE OR EMISSIONS | E112 | | | ROG: (9) [RULE 1168,10-3-2003;RULE 1168,1-7-2005;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | |
| RULE 219 EXEMPT EQUIPMENT, COATING EQUIPMENT, LOW USE OR EMISSIONS | E113 | | | ROG: (5) [RULE 1128,3-8-1996;RULE 1171,11-7-2003;RULE 1171,2-1-2008] | |

- * (1)(1A)(1B) Denotes RECLAIM emission factor
(3) Denotes RECLAIM concentration limit
(5)(5A)(5B) Denotes command and control emission limit
(7) Denotes NSR applicability limit
(9) See App B for Emission Limits
(2)(2A)(2B) Denotes RECLAIM emission rate
(4) Denotes BACT emission limit
(6) Denotes air toxic control rule limit
(8)(8A)(8B) Denotes 40 CFR limit(e.g. NSPS, NESHAPS, etc.)
(10) See Section J for NESHAP/MACT requirements

** Refer to Section F and G of this permit to determine the monitoring, recordkeeping and reporting requirements for this device.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

**The following sub-section provides an index
to the devices that make up the facility
description sorted by device ID.**

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| D1 | 1 | 1 | 1 |
| D2 | 1 | 1 | 1 |
| D3 | 1 | 1 | 1 |
| D4 | 1 | 1 | 1 |
| D5 | 1 | 1 | 1 |
| D7 | 1 | 1 | 1 |
| D8 | 2 | 1 | 1 |
| D10 | 2 | 1 | 1 |
| D12 | 2 | 1 | 1 |
| D15 | 2 | 1 | 1 |
| D16 | 29 | 2 | 0 |
| D17 | 29 | 2 | 0 |
| D18 | 30 | 2 | 0 |
| D19 | 30 | 2 | 0 |
| D20 | 54 | 3 | 0 |
| D21 | 54 | 3 | 0 |
| D22 | 54 | 3 | 0 |
| D24 | 55 | 3 | 0 |
| D36 | 55 | 4 | 1 |
| D40 | 55 | 4 | 1 |
| D44 | 57 | 5 | 1 |
| D48 | 58 | 7 | 1 |
| C49 | 58 | 7 | 1 |
| D88 | 56 | 4 | 1 |
| D89 | 56 | 4 | 1 |
| D90 | 56 | 4 | 1 |
| D95 | 2 | 1 | 1 |
| C96 | 58 | 8 | 1 |
| D98 | 3 | 1 | 1 |
| D99 | 3 | 1 | 1 |
| D101 | 3 | 1 | 1 |
| E102 | 58 | 9 | 1 |
| E104 | 58 | 9 | 1 |
| E105 | 59 | 9 | 1 |
| E107 | 59 | 9 | 1 |
| E108 | 59 | 9 | 1 |

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| E111 | 59 | 9 | 1 |
| E112 | 59 | 9 | 1 |
| E113 | 59 | 9 | 1 |
| D115 | 3 | 1 | 1 |
| D116 | 4 | 1 | 1 |
| D117 | 5 | 1 | 1 |
| D118 | 5 | 1 | 1 |
| D119 | 6 | 1 | 1 |
| D120 | 6 | 1 | 1 |
| D121 | 7 | 1 | 1 |
| D122 | 8 | 1 | 1 |
| D123 | 8 | 1 | 1 |
| D124 | 9 | 1 | 1 |
| D125 | 9 | 1 | 1 |
| D126 | 10 | 1 | 1 |
| D127 | 11 | 1 | 1 |
| D128 | 11 | 1 | 1 |
| D129 | 12 | 1 | 1 |
| D131 | 12 | 1 | 1 |
| D133 | 13 | 1 | 1 |
| D134 | 14 | 1 | 1 |
| D135 | 31 | 2 | 0 |
| D137 | 31 | 2 | 0 |
| D138 | 32 | 2 | 0 |
| D139 | 33 | 2 | 0 |
| D146 | 14 | 1 | 1 |
| D147 | 56 | 4 | 1 |
| D148 | 56 | 4 | 1 |
| D149 | 15 | 1 | 1 |
| D152 | 16 | 1 | 1 |
| D153 | 16 | 1 | 1 |
| D156 | 57 | 5 | 1 |
| C158 | 57 | 5 | 1 |
| D159 | 16 | 1 | 1 |
| D160 | 17 | 1 | 1 |
| D162 | 17 | 1 | 1 |

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| D163 | 17 | 1 | 1 |
| D164 | 18 | 1 | 1 |
| D165 | 55 | 3 | 0 |
| D168 | 18 | 1 | 1 |
| D169 | 18 | 1 | 1 |
| D170 | 57 | 5 | 1 |
| D172 | 19 | 1 | 1 |
| D173 | 20 | 1 | 1 |
| D174 | 20 | 1 | 1 |
| D175 | 21 | 1 | 1 |
| D176 | 22 | 1 | 1 |
| D177 | 28 | 1 | 2 |
| D178 | 22 | 1 | 1 |
| D179 | 23 | 1 | 1 |
| D180 | 24 | 1 | 1 |
| D181 | 24 | 1 | 1 |
| D182 | 25 | 1 | 1 |
| D183 | 25 | 1 | 1 |
| D200 | 34 | 2 | 0 |
| D202 | 34 | 2 | 0 |
| D206 | 35 | 2 | 0 |
| D207 | 35 | 2 | 0 |
| D209 | 36 | 2 | 0 |
| D211 | 37 | 2 | 0 |
| D214 | 37 | 2 | 0 |
| D215 | 38 | 2 | 0 |
| D217 | 39 | 2 | 0 |
| D219 | 39 | 2 | 0 |
| D221 | 40 | 2 | 0 |
| D223 | 26 | 1 | 1 |
| D224 | 41 | 2 | 0 |
| D225 | 41 | 2 | 0 |
| D226 | 41 | 2 | 0 |
| D228 | 41 | 2 | 0 |
| D229 | 42 | 2 | 0 |
| D230 | 42 | 2 | 0 |

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| D231 | 42 | 2 | 0 |
| D232 | 42 | 2 | 0 |
| D233 | 43 | 2 | 0 |
| D234 | 43 | 2 | 0 |
| D235 | 43 | 2 | 0 |
| D236 | 43 | 2 | 0 |
| D237 | 44 | 2 | 0 |
| D238 | 44 | 2 | 0 |
| D239 | 44 | 2 | 0 |
| D240 | 44 | 2 | 0 |
| D241 | 45 | 2 | 0 |
| D242 | 45 | 2 | 0 |
| D243 | 45 | 2 | 0 |
| D244 | 45 | 2 | 0 |
| D246 | 46 | 2 | 0 |
| D248 | 46 | 2 | 0 |
| D249 | 46 | 2 | 0 |
| D250 | 46 | 2 | 0 |
| D252 | 47 | 2 | 0 |
| D253 | 47 | 2 | 0 |
| D255 | 47 | 2 | 0 |
| D256 | 47 | 2 | 0 |
| D257 | 48 | 2 | 0 |
| D258 | 48 | 2 | 0 |
| D259 | 27 | 1 | 1 |
| D260 | 48 | 2 | 0 |
| D261 | 49 | 2 | 0 |
| D262 | 49 | 2 | 0 |
| D263 | 49 | 2 | 0 |
| D264 | 50 | 2 | 0 |
| D265 | 50 | 2 | 0 |
| D266 | 50 | 2 | 0 |
| D267 | 50 | 2 | 0 |
| D268 | 51 | 2 | 0 |
| D269 | 51 | 2 | 0 |
| D270 | 51 | 2 | 0 |

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: DEVICE ID INDEX

| Device Index For Section D | | | |
|----------------------------|--------------------|---------|--------|
| Device ID | Section D Page No. | Process | System |
| D271 | 51 | 2 | 0 |
| D272 | 52 | 2 | 0 |
| D273 | 52 | 2 | 0 |
| D274 | 52 | 2 | 0 |
| D275 | 52 | 2 | 0 |
| D276 | 28 | 1 | 1 |
| D284 | 53 | 2 | 0 |
| D285 | 53 | 2 | 0 |
| D286 | 53 | 2 | 0 |
| D287 | 53 | 2 | 0 |
| D288 | 54 | 2 | 0 |

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

FACILITY CONDITIONS

F1.1 The operator shall limit the material processed to no more than 2000 lb(s) in any one year.

For the purpose of this condition, material processed shall be defined as 1,1,1 trichloroethane.

[H&S 44300, 7-1-1988]

F9.1 Except for open abrasive blasting operations, the operator shall not discharge into the atmosphere from any single source of emissions whatsoever any air contaminant for a period or periods aggregating more than three minutes in any one hour which is:

(a) As dark or darker in shade as that designated No.1 on the Ringelmann Chart, as published by the United States Bureau of Mines; or

(b) Of such opacity as to obscure an observer's view to a degree equal to or greater than does smoke described in subparagraph (a) of this condition.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

F14.2 The operator shall not purchase diesel fuel containing sulfur compounds in excess of 15 ppm by weight as supplied by the supplier.

[RULE 431.2, 5-4-1990; RULE 431.2, 9-15-2000]

F48.1 The operator shall not operate at this facility non chain driven, uncontrolled charbroiler exceeding the opacity limits specified in Rule 401.

[RULE 401, 3-2-1984; RULE 401, 9-11-1998]

DEVICE CONDITIONS

A. Emission Limits

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

A63.1 The operator shall limit emissions from this equipment as follows:

| CONTAMINANT | EMISSIONS LIMIT |
|-------------|---|
| VOC | Less than or equal to 10 LBS IN ANY ONE DAY |

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D21, D22]

B. Material/Fuel Type Limits

B27.2 The operator shall not use abrasive material (except for abrasive containing nickel) containing any carcinogenic compounds identified in the SCAQMD Rule 1401, as amended 18-aug-2000.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D156]

B27.4 The operator shall not use materials containing any compounds identified in the SCAQMD Rule 1401, as amended 12/07/1990.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D21, D22, D165]

B59.1 The operator shall only use the following material(s) in this device :

Diesel fuel

[RULE 1140, 8-2-1985]

[Devices subject to this condition : D170]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

B59.2 The operator shall only use the following material(s) in this device :

diesel fuel or bio-diesel

[**RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005]**

[Devices subject to this condition : D224, D225, D226, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D246, D248, D249, D250, D252, D253, D255, D256, D257, D258, D262, D263, D264, D265, D266, D267, D268, D269, D270, D271, D272, D273, D274, D275, D284, D285, D286, D287, D288]

C. Throughput or Operating Parameter Limits

C1.1 The operator shall limit the operating time to no more than 200 hour(s) in any one year.

[**RULE 1110.2, 6-3-2005; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(b)(1)-Modeling, 5-10-1996; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999; RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]**

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D12, D15, D95, D99, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D152, D153, D160, D168, D169, D172, D173, D174, D175, D176, D178, D179, D180, D181, D182, D183, D223, D259, D276]

C1.2 The operator shall limit the operating time to no more than 125 hour(s) in any one year.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]**

[Devices subject to this condition : D10]

C1.3 The operator shall limit the operating time to no more than 100 hour(s) in any one year.

[**RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]**

[Devices subject to this condition : D98]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.6 The operator shall limit the gasoline dispensed to no more than 240000 gallon(s) per year.

[RULE 1401, 8-18-2000]

[Devices subject to this condition : D147]

C1.7 The operator shall limit the gasoline dispensed to no more than 20000 gallon(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 10-20-2000]

[Devices subject to this condition : D147]

C1.8 The operator shall limit the operating time to no more than 199 hour(s) in any one year.

[RULE 1110.2, 6-3-2005; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996]

[Devices subject to this condition : D159, D164]

C1.9 The operator shall limit the coating and solvent usage to no more than 4 gallon(s) per day.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]

C1.10 The operator shall limit the coating and solvent usage to no more than 88 gallon(s) per month.

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]

C1.11 The operator shall limit the maintenance testing to no more than 50 hour(s) in any one year.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D95, D149, D160; D169, D173, D174, D175, D176, D223, D259, D276]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.12 The operator shall limit the operating time to no more than 1092 in any one calendar year.

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D177]

C1.13 The operator shall limit the natural gas fuel usage to no more than 15.569 MM cubic feet in any one calendar month.

The fuel usage limit of 15.569 mmcf/month is the total fuel to be used in the five boilers.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D214, D215, D217, D219, D221]

C1.14 The operator shall limit the operating time to no more than 300 hour(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D224, D225, D226, D228, D229, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D246, D248, D249, D250, D252, D253, D262, D263, D264, D265]

C1.16 The operator shall limit the operating time to no more than 22 hour(s) in any one day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005]

[Devices subject to this condition : D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D255, D256, D257, D258, D262, D263, D264, D265, D284, D285, D286, D287, D288]

C1.17 The operator shall limit the operating time to no more than 12 hour(s) in any one day.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005]

[Devices subject to this condition : D243, D244, D248, D252]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.18 The operator shall limit the operating time to no more than 330 hour(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005]

[Devices subject to this condition : D255, D256, D257, D258]

C1.19 The operator shall limit the fuel usage to no more than 6.156 MM cubic feet in any one calendar month.

This limit shall be based on the total combined limit for equipment D260 and D261.

This equipment shall only use natural gas as a fuel.

The operator shall identify the primary and secondary heater fuel usage..

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D260, D261]

C1.20 The operator shall limit the maintenance testing to no more than 30 hour(s) in any one year.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 1470, 6-1-2007]

[Devices subject to this condition : D15, D99, D153, D168]

C1.21 The operator shall limit the fuel usage to no more than 2.637 MM cubic feet in any one calendar month.

This equipment shall only use natural gas as a fuel.

The operator shall identify the primary and secondary heater.

This condition only applies to the secondary heater.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D260, D261]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

C1.22 The operator shall limit the maintenance testing to no more than 34 hour(s) in any one year.

[RULE 1470, 6-1-2007]

[Devices subject to this condition : D152, D164, D172]

C1.23 The operator shall limit the operating time to no more than 200 hour(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D266, D267, D268, D269, D270, D271, D272, D273, D274]

C1.24 The operator shall limit the operating time to no more than 160 hour(s) in any one calendar month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002]

[Devices subject to this condition : D275]

C1.26 The operator shall limit the operating time to no more than 572 hour(s) in any one month.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005]

[Devices subject to this condition : D284, D285, D286, D287, D288]

C6.1 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 0.25 inches water column.

The operator shall to comply with this condition, monitor the differential pressure as specified in condition D12.2..

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D21, D22, D24, D165]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- C6.2 The operator shall use this equipment in such a manner that the differential pressure being monitored, as indicated below, does not exceed 5 inches water column.

The operator shall to comply with this condition, monitor the differential pressure as specified in condition D12.2..

[RULE 1303, 10-20-2000; **RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : C158]

- C177.1 The operator shall set and maintain the fuel injection timing of the engine at 4 degrees retarded relative to standard timing.

[**RULE 1303(a)(1)-BACT, 5-10-1996**; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D7, D8, D10, D15, D95, D98, D99, D153, D160, D162, D163]

D. Monitoring/Testing Requirements

- D12.1 The operator shall install and maintain a(n) timer to accurately indicate the elapsed operating time of the engine.

[RULE 1110.2, 6-3-2005; **RULE 1303(b)(1)-Modeling, 5-10-1996**; RULE 1303(b)(1), 10-20-2000; **RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996**; **RULE 2005, 10-15-1993**; **RULE 2005, 4-9-1999**; **RULE 2012, 12-7-1995**; RULE 2012, 4-9-1999; **RULE 3004(a)(4)-Periodic Monitoring, 8-11-1995**; **RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997**]

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D10, D12, D15, D95, D98, D99, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D152, D153, D159, D160, D162, D163, D164, D168, D169, D172, D173, D174, D175, D176, D177, D178, D179, D180, D181, D182, D183, D223, D259, D276]

- D12.2 The operator shall install and maintain a(n) differential pressure gauge to accurately indicate the differential pressure across the filter.

[RULE 1303, 10-20-2000; **RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D21, D22, D24, C158, D165]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- D12.3 The operator shall install and maintain a(n) flow meter to accurately indicate the flue gas flow in the flue gas recirculation system.

For the purpose of this condition a flue gas flow regulator that indicates the percent open setting in the FGR system may be used instead of a flow meter.

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D16, D18]

- D12.4 The operator shall install and maintain a(n) non-resettable totalizing fuel flow meter to accurately indicate the fuel usage of the equipment.

[RULE 2012, 12-7-1995; RULE 2012, 4-9-1999]

[Devices subject to this condition : D16, D17, D18, D19, D206, D207, D209, D211, D214, D215, D217, D219, D221, D260, D261]

- D12.8 The operator shall install and maintain a(n) timer to accurately indicate the elapsed operating time from the pressure washer.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 12-6-2002; RULE 1401, 3-4-2005; RULE 2012, 5-6-2005]

[Devices subject to this condition : D224, D225, D226, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D246, D248, D249, D250, D252, D253, D255, D256, D257, D258, D262, D263, D264, D265, D266, D267, D268, D269, D270, D271, D272, D273, D274, D275, D284, D285, D286, D287, D288]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D29.1 The operator shall conduct source test(s) for the pollutant(s) identified below.

| Pollutant(s) to be tested | Required Test Method(s) | Averaging Time | Test Location |
|---------------------------|-------------------------|----------------------------------|---------------|
| NOX emissions | District method 100.1 | District-approved averaging time | Outlet |
| CO emissions | District method 100.1 | District-approved averaging time | Outlet |

A. SOURCE TESTING SHALL BE CONDUCTED WITHIN 30 DAYS AFTER ACHIEVING MAXIMUM PRODUCTION RATE AT WHICH THE EQUIPMENT WILL BE OPERATED, BUT NO LATER THAN 90 DAYS AFTER INITIAL START-UP

B. THE SOURCE TEST SHALL BE DONE TO VERIFY EMISSIONS LIMITS FOR NOX AND CO CO, 20 PPMV AND 50 PPMV RESPECTIVELY

C. THE TEST SHALL BE CONDUCTED FOR 15 MINUTES EACH WHILE OPERATING AT NORMAL LOAD, HIGH, LOW AND AVERAGE FIRING RATES

D. TWO COMPLETE COPIES OF SOURCE TEST REPORTS (INCLUDE THE APPLICATION NUMBER AND A COPY OF THE PERMIT IN THE REPORT) SHALL BE SUBMITTED TO THE DISTRICT (ADDRESSED TO SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT, ATTN: ROY OLIVARES, P.O. BOX 4941, DIAMOND BAR, CA 91765). THE RESULTS IN WRITING SHALL BE SUBMITTED WITHIN 45 DAYS AFTER THE SOURCE TEST IS COMPLETED. IT SHALL INCLUDE, BUT NOT LIMITED TO EMISSIONS RATE IN POUNDS PER HOUR AND CONCENTRATION IN PPMV AT THE OUTLET OF THE HEATER

E. TESTING LABORATORY CERTIFIED BY THE CALIFORNIA AIR RESOURCES BOARD IN THE REQUIRED TEST METHODS FOR CRITERIA POLLUTANT TO BE MEASURED, AND IN COMPLIANCE WITH DISTRICT RULE 304 (NO CONFLICT OF INTEREST) SHALL CONDUCT THE TEST

F. SAMPLING FACILITIES SHALL COMPLY WITH THE ATTACHED AQMD "GUIDELINES FOR CONSTRUCTION OF SAMPLING AND TESTING FACILITIES", PURSUANT TO RULE 217.

[RULE 1146, 11-17-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 2005, 5-6-2005]

[Devices subject to this condition : D260, D261]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D322.1 The operator shall perform a weekly inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D21, D22, D24, C96, D165]

D322.2 The operator shall perform a weekly inspection to check for the water wash integrity.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D20]

D322.3 The operator shall perform annual inspection of the equipment and filter media for leaks, broken or torn filter media, and improperly installed filter media.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C158]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D323.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions; whenever visible emissions are observed, and on a semi-annual basis, at least, unless the equipment did not operate during the entire semi-annual period. The routine semi-annual inspection shall be conducted while the equipment is in operation and during daylight hours.

If any visible emissions (not including condensed water vapor) are detected that last more than three minutes in any one hour, the operator shall verify and certify within 24 hours that the equipment causing the emission and any associated air pollution control equipment are operating normally according to their design and standard procedures and under the same conditions under which compliance was achieved in the past, and either:

- 1). Take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit; or
- 2). Have a CARB-certified smoke reader determine compliance with the opacity standard, using EPA Method 9 or the procedures in the CARB manual "Visible Emission Evaluation", within three business days and report any deviations to AQMD.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions;
- 3). Date and time visible emission was abated; and
- 4). All visible emission observation records by operator or a certified smoke reader.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D44, D48, C49, C96, D177]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

D330.1 The operator shall have a person that has been trained in accordance with Rule 461 conduct a semi-annual inspection of the gasoline transfer and dispensing equipment. The first inspection shall be in accordance with Rule 461, Attachment B, the second inspection shall be in accordance with Rule 461, Attachment C, and the subsequent inspections shall alternate protocols. The operator shall keep records of the inspection and the repairs in accordance to Rule 461 and Section K of this Permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D36, D40, D88, D89, D90]

D332.1 The operator shall determine compliance with the CO emission limit(s) by conducting a test at least once every five years using a portable analyzer and AQMD-approved test method or, if not available, a non-AQMD approved test method. The test shall be conducted when the equipment is operating under normal conditions to demonstrate compliance with Rule 1146.1 concentration limit. The operator shall comply with all general testing, reporting, and recordkeeping requirements in Sections E and K of this permit.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D200, D202]

D381.1 The operator shall conduct an inspection for visible emissions from all stacks and other emission points of this equipment whenever there is a public complaint of visible emissions, whenever visible emissions are observed, and on an annual basis, at least, unless the equipment did not operate during the entire annual period. The routine annual inspection shall be conducted while the equipment is in operation and during daylight hours. If any visible emissions (not including condensed water vapor) are detected, the operator shall take corrective action(s) that eliminates the visible emissions within 24 hours and report the visible emissions as a potential deviation in accordance with the reporting requirements in Section K of this permit.

The operator shall keep the records in accordance with the recordkeeping requirements in Section K of this permit and the following records:

- 1). Stack or emission point identification;
- 2). Description of any corrective actions taken to abate visible emissions; and
- 3). Date and time visible emission was abated.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C158, D170]

E. Equipment Operation/Construction Requirements

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E17.1 The operator shall not use more than 1 of the following items simultaneously:

Device ID: D200 [Heater]

Device ID: D202 [Heater]

[RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D200, D202]

E71.1 The operator shall only operate this equipment during emergencies resulting in an interruption of service of the primary power supply or during stage II or III electrical emergency declared by the California Independent system operator (in addition to maintenance and testing of this engine)..

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D149, D169, D173]

E71.2 The operator shall only operate this equipment using the manufacturers recommendation for the installation, operation and maintenance of the phase one and phase two vapor recovery equipment. The manufacturers manuals shall be readily accessible on site and made available to District representatives upon request.

[RULE 461, 6-3-2005]

[Devices subject to this condition : D147]

E71.3 The operator shall only operate this equipment during operation beyond 50 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

[RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000]

[Devices subject to this condition : D174]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- E71.4 The operator shall only operate this equipment during operation beyond 50 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D95, D149, D160, D169, D175, D179, D180, D181, D182, D183, D223]

- E71.5 The operator shall only operate this equipment during operation beyond 50 hours per year, this engine shall only operate during emergencies resulting in an interruption of service of the primary power supply or during stage II or III electrical emergency declared by the electrical grid operator. Operators may use this engine as part of interruptible electrical service program.

An interruptible electric service program is a program in which the facility receives payment or reduced rate in return for a requirement to reduce its electric load on the grid when requested to do so by the utility, the grid operator, or other organization.

[RULE 1303(a)-BACT, 5-10-1996]

[Devices subject to this condition : D176, D182, D259, D276]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

- E71.6 The operator shall only operate this equipment during operation beyond 30 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007**]

[Devices subject to this condition : D15, D98, D99, D133, D146, D153, D159, D162, D163, D168]

- E71.7 The operator shall only operate this equipment during operation beyond 20 hours per year for maintenance and testing is allowed only in the event of loss of grid power or up to 30 minutes prior to a rotating outage provided that: 1) the electrical grid operator or electric utility has ordered rotating outages in the control area where the engine is located or has indicated that it expects to issue such an order at a certain time; and 2) the engine is located in a utility service block that is subject to the rotating outage.

Engine operation shall be terminated immediately after the utility distribution company advises that a rotating outage is no longer imminent or in effect.

[**RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 12-6-2002; RULE 1470, 6-1-2007**]

[Devices subject to this condition : D3, D4, D5, D10]

- E102.1 The operator shall discharge dust collected in this equipment only into closed containers.

[**RULE 1303, 10-20-2000; RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : C158]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E116.1 This engine shall not be used as part of a demand response program using interruptible service contract in which a facility receives a payment or reduced rates in return for reducing its electric load on the grid when requested to do so by the utility or the grid operator.

[**RULE 1303(a)-BACT, 5-10-1996**; RULE 1303(a), 12-6-2002; RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168, D179, D180, D181, D183, D223, D259]

E175.1 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 2 inches thick

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D21, D22, D24]

E175.2 The operator shall not use this equipment unless all exhaust air passes through the following:

filter media at least 1.5 inches thick

[**RULE 1303(a)(1)-BACT, 5-10-1996**]

[Devices subject to this condition : D165]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E193.1 The operator shall operate and maintain this equipment as follows:

ALL PERMIT CONDITIONS APPLICABLE TO THE EQUIPMENT DESCRIBED IN THE PREVIOUS PERMIT TO OPERATE N15788 SHALL REMAIN IN EFFECT UNTIL THE NEW OR MODIFIED EQUIPMENT IS CONSTRUCTED AND OPERATED AS DESCRIBED IN THIS NEW PERMIT. THIS PERMIT TO CONSTRUCT/OPERATE SHALL BECOME INVALID IF THE MODIFICATION AS DESCRIBED IN THE EQUIPMENT DESCRIPTION HAS NOT BEEN COMPLETED WITHIN ONE YEAR FROM THE ISSUE DATE. IF THE MODIFICATION HAS NOT BEEN COMPLETED WITHIN ONE YEAR FROM THE ISSUE DATE OF THE PERMIT

A WRITTEN REQUEST SHALL BE SUBMITTED TO THE AQMD (ATTENTION: RANDY MATSUYAMA) TO REINSTATE THE PREVIOUSLY INACTIVATED PERMIT TO OPERATE. A NEW APPLICATION SHALL BE FILED IF THERE ARE PLANS TO CONTINUE WITH THE MODIFICATION. FURTHERMORE, THIS CONDITION DOES NOT ALLOW ANY TIME EXTENSIONS TO ANY MODIFICATIONS REQUIRED BY THE CALIFORNIA AIR RESOURCES BOARD OR AQMD

[RULE 461, 3-7-2008]

[Devices subject to this condition : D36, D40, D89, D90]

E193.2 The operator shall operate and maintain this equipment as follows:

ALL PHASE I AND PHASE II VAPOR RECOVERY EQUIPMENT AT THIS FACILITY SHALL BE INSTALLED, OPERATED AND MAINTAINED TO MEET ALL CALIFORNIA AIR RESOURCES BOARD CERTIFICATION REQUIREMENTS

[RULE 461, 3-7-2008]

[Devices subject to this condition : D88, D89, D90]

E202.1 The operator shall clean and maintain this equipment according to the following specifications:

Thoroughly clean the ionizers and collector cells quarterly

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C49]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

E202.2 The operator shall clean and maintain this equipment according to the following specifications:

the diesel catalyst shall be inspected once every calendar year and cleaned, if necessary. If cleaning is necessary, all loose soot deposits shall be removed and the catalyst shall be washed according to manufacturers specifications

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D133, D146]

E202.3 The operator shall clean and maintain this equipment according to the following specifications:

the engine shall not be operated without the use of an automatic air to fuel ratio controller which shall be maintained and kept in proper operating conditions at all times as specified by the manufacturer

the catalytic converter temperature and exhaust oxygen concentration shall be maintained within the effective operating range of the catalytic converter as specified by the manufacturer

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D134, D173, D174, D176, D178, D259, D276]

E202.4 The operator shall clean and maintain this equipment according to the following specifications:

Records shall be maintained of inspections and maintenance of the burners

The operator shall follow the procedures specified by the manufacturer to tune-up and maintain the combustion system (including but not limited to the burner and air/fuel control device) of this heater

Manufacturers maintenance procedures shall be kept by the operator and made available at the request of AQMD

[RULE 1303(a)(1)-BACT, 5-10-1996; RULE 1303(a)(1)-BACT, 10-20-2000; RULE 2005, 4-9-1999]

[Devices subject to this condition : D135, D137, D138, D139, D260, D261]

H. Applicable Rules

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.1 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 1122 |

[RULE 1122, 10-1-2004]

[Devices subject to this condition : E105]

H23.2 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| VOC | District Rule | 109 |
| PM | District Rule | 481 |

[RULE 109, 5-2-2003; RULE 481, 1-11-2002]

[Devices subject to this condition : D20, D21, D22, D24, D165]

H23.3 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|--------------|------------------|--------------|
| Refrigerants | District Rule | 1415 |
| Refrigerants | 40CFR82, SUBPART | F |

[RULE 1415, 10-14-1994; 40CFR 82 Subpart F, 5-14-1993]

[Devices subject to this condition : E102]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.4 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| CO | District Rule | 1146 |

This CO emissions (concentration) shall be tested at least once per year per Rule 1146 (d)(6).

[RULE 1146, 11-17-2000]

[Devices subject to this condition : D16, D17, D18, D19, D135, D137, D138, D139, D206, D207, D209, D211, D214, D215, D217, D219, D221]

H23.5 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM | District Rule | 1140 |

[RULE 1140, 2-1-1980; RULE 1140, 8-2-1985]

[Devices subject to this condition : D170]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.6 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM | District Rule | 1470 |

[RULE 1470, 6-1-2007]

[Devices subject to this condition : D1, D2, D3, D4, D5, D7, D8, D10, D12, D15, D95, D98, D99, D133, D146, D149, D152, D153, D159, D160, D162, D163, D164, D168, D169, D172, D175, D179, D180, D181, D183, D223]

H23.8 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| CO | District Rule | 1146.1 |

[RULE 1146.1, 5-13-1994]

[Devices subject to this condition : D200, D202]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.9 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| CO | District Rule | 1146 |

7. THE OPERATOR OF THIS EQUIPMENT SHALL COMPLY WITH SOURCE TESTING REQUIREMENTS IN SUBDIVISION (d)(6)--COMPLIANCE DETERMINATION OF RULE 1146.

8. THE OPERATOR OF THIS EQUIPMENT SHALL COMPLY WITH PERIODIC MONITORING REQUIREMENTS OF RULE 1146 (c)(8).

[RULE 1146, 11-17-2000; RULE 1146, 9-5-2008]

[Devices subject to this condition : D260, D261]

H23.11 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| PM | District Rule | 1472 |

[RULE 1472, 3-7-2008]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

H23.12 This equipment is subject to the applicable requirements of the following rules or regulations:

| Contaminant | Rule | Rule/Subpart |
|-------------|---------------|--------------|
| SOX | District Rule | 431.1 |

[RULE 431.1, 6-12-1998]

[Devices subject to this condition : D16, D17, D18, D19, D101, D115, D116, D117, D118, D119, D120, D121, D122, D123, D124, D125, D126, D127, D128, D129, D134, D135, D137, D138, D139, D173, D174, D176, D178, D182, D200, D202, D206, D207, D209, D211, D214, D215, D217, D219, D221, D259, D260, D261]

J. Rule 461

J110.1 The operator shall use, except for diesel transfer, the phase II vapor recovery system in full operation whenever gasoline from this equipment is dispensed to motor vehicles as defined in Rule 461. This system shall be installed, operated and maintained to meet all CARB certification requirements.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D88, D89, D90, D147]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J373.1 The operator shall comply with the following gasoline transfer and dispensing requirements:

a). At least seventy-two (72) hours prior to back-filling any underground storage tank or piping, the SCAQMD shall be notified by e-mail at r461backfill@aqmd.gov or by facsimile at telephone number (909) 396-3606. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the back-filling procedure. The backfilling procedure shall not commence until inspected by a District representative.

b). As required by AQMD Rule 461 or CARB Executive Order, a static pressure leak decay test shall be conducted to demonstrate that the storage tanks, the remote and/or nozzle vapor recovery check valves, associated vapor return piping and fittings are free from vapor leaks. The test shall be conducted in accordance with CARB Test Procedure Method TP-201.3. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at R461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the static pressure leak decay test.

c). Depending on the system configuration, a pressure integrity test of the drop tube/drain valve assembly shall be conducted to quantify the pressure integrity of both the drop tube and drain valve seal or a pressure integrity test of the drop tube overflow prevention device and spill container drain and the pressure integrity of the spill container drain valve. Either test shall be conducted as a reverification test and the test shall be conducted in accordance with test procedure method TP-201.1C or TP-201.1D, respectively. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the of the pressure integrity test of drop tube/drain valve assembly or pressure integrity test of the drop tube overflow prevention device and spill container drain valve.

d). A leak rate and cracking pressure test of pressure/vacuum relief vent valves shall be conducted within thirty (30) days after the start of operation of the (add type) Phase I EVR equipment and at least once every three (3) years thereafter to determine the pressure and vacuum at which the pressure/vacuum vent valve actuates, and to determine the volumetric leak rate at a given pressure. The test shall be conducted in accordance with the test procedure method TP-201.1E. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of test. This test result shall be kept on site for three (3) years and made available to district representatives upon request.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the leak rate and cracking pressure of pressure/vacuum relief vent valves test.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

e). A static torque test of rotatable Phase I adaptors shall be conducted as a reverification test to quantify the amount of static torque required to start the rotation of the rotatable Phase I adaptors. The test shall be conducted in accordance with the test procedure method outlined in TP-201-1B.. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at (909) 396-2606 at least 72 hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractor; the location of the facility; and the scheduled start and completion dates of the static torque test of rotatable Phase I adaptors.

f). The Phase II vapor recovery systems shall be installed, operated, and maintained such that the maximum allowable pressure through the system including nozzle, vapor hose, swivels, and underground piping does not exceed the dynamic back pressures described by the California Air Resources Board (CARB) Executive Order by which the system was certified:

| Nitrogen Flowrates (CFH) | Dynamic Back Pressure (Inches of Water) |
|--------------------------|---|
|--------------------------|---|

| | |
|----|------|
| 60 | 0.35 |
|----|------|

| | |
|----|------|
| 80 | 0.62 |
|----|------|

As required by AQMD Rule 461 or CARB Executive Order, dynamic back pressure tests shall be conducted to determine the Phase II system vapor recovery back pressures. The tests shall be conducted in accordance with CARB Test Procedure Method TP-201.4. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at R461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the dynamic back pressure test.

The test shall be conducted as frequently as that required by the most recent amendment to Rule 461 or CARB Executive Order requirements, whichever is more stringent.

g). If the CARB Executive Order requires the installation of a liquid removal device, a liquid removal rate test shall be conducted to demonstrate the removal of gasoline from the vapor passage of the coaxial hose. The test shall be conducted within thirty days of initial installation and in accordance with CARB test procedure Method TP-201.6. Results shall be submitted to the AQMD, Engineering and Compliance, within seventy-two (72) hours of the test.

The AQMD shall be notified by e-mail at r461testing@aqmd.gov or by facsimile at telephone number (909) 396-3606 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator; the name of the contractors; the location of the facility; and the scheduled start and completion dates of the liquid removal rate test.

The testing frequency for the above mentioned tests shall be conducted in accordance with the most recent AQMD Rule 461 amendment or CARB Executive Order requirements, whichever is more stringent.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

All records and test results that are required to be maintained by Rule 461 shall be kept on site and made available to AQMD representatives upon request.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D36, D40, D88, D89, D90] .

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

J397.1 The operator shall comply with the following CARB Executive Order G-70-193:

1. The owner or operator of this equipment shall conduct a physical inspection of the equipment and manually monitor the system gauge levels during gasoline dispensing on a daily operating basis per site. The equipment shall operate within the following gauge levels:

- | | |
|------------------------------|--------------------|
| a) Vapor return line vacuum: | 35" to 65" wc |
| b) Gasoline supply pressure: | 27 psig to 35 psig |
| c) Cargo tank pressure: | less than 18" wc |

All physical inspections and gauge observations shall be recorded in a systems log and be kept on board the mobile fueler at all times.

2. If a violation of the gauge ranges specified in conditions 1a, 1b, or 1c occurs, the owner or operator of this equipment shall:

- a) Record the date, time period, and fuel totalizing meter reading when the system first began to fail to operate within the specified range.
- b) Record the date and time that contact was made with an authorized representative to have the system inspected and repaired.
- c) Record the date and time that the authorized representative inspected the system, provide a written description of the repairs performed, and record the fuel totalizing meter reading.

3. This equipment shall cease all gasoline dispensing operations when any one of the following conditions occur:

- a) One of the jet pumps is disabled;
- b) Failing to achieve the minimum operating vacuum of 35" wc within five seconds after the system has been activated for three consecutive dispensing episodes;
- c) A vacuum level below 15" wc for more than three seconds after the system has reached 35" wc;
- d) A vacuum level above 85" wc during a dispensing episode to non-ORVR vehicles;
- e) Except during testing operations, a closed valve at the vapor return line connection to each jet pump;
- f) A pressure in the cargo tank headspace exceeding 18" wc for more than five minutes (accumulated) during any sixty minute gasoline dispensing period;
- g) Except during repair operations, an open drain valve in the liquid drop out pot;
- h) Except during testing operations, a closed drain valve at the liquid drop out pot in the liquid removal

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

line;

i) Any observation of breaks, cracks, or holes in the tank insulation, which affects the insulating properties or durability of the insulation;

j) The accumulated length of all tears of the nozzle boot (including rips, slits, cracks, etc.) exceeds 0.5" in length; or

k) The faceplate and fill pipe interface cannot achieve a seal of at least 25 percent of the accumulated circumference of the faceplate.

4. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a vapor return line vacuum integrity test shall be conducted and pass in accordance with Exhibit 3 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the vapor return line vacuum integrity test.

5. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a fill pipe pressure regulation fueling test shall be conducted and pass in accordance with Exhibit 4 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the fill pipe pressure regulation fueling test.

6. Within thirty (30) days of initial operation and at least once every twelve months from the previous test, a ten gallon per minute flowrate limitation test shall be conducted and pass in accordance with Exhibit 5 of CARB Executive Order G-70-193. Results shall be submitted to the AQMD, Office of Engineering and Compliance, within forty-eight (48) hours of test.

The AQMD shall be notified at telephone number (909) 396-3886 at least seventy-two (72) hours prior to testing. Such notification shall include the name of the owner or operator of this equipment; the name of the testing contractor; the location of the mobile fueler; and the scheduled start and completion dates of the ten gallon per minute limitation test.

7. The individual and company performing any maintenance on any part of the vapor recovery system shall provide at a minimum for the owner or operator of the mobile fueler, a chronological record consisting of the following information for the mobile fueler's maintenance log. The date of service, name of maintenance technician, a contact phone number, a description of and location of any equipment replaced including appropriate test results, and a description of the system problems repaired.

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

9. Except for necessary inspections due to equipment failures, and for scheduled maintenance and repairs; the mobile fueler dome hatch shall remain closed and latched at all times. Furthermore, the mobile fueler dome hatch shall remain closed and latched until the head space pressure is less than 2" wc.

8. A current CARB certification decal shall be displayed on the mobile fueler in a manner approved by the executive officer.

10. All physical inspection and gauge observation records; all test results; and all maintenance records as required by this CARB Executive Order shall be prepared, shall be retained for two years, and shall be kept within the mobile fueler and made available to district representatives upon request.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D147]

K. Record Keeping/Reporting

K67.1 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

For architectural applications where no thinners, reducers, or other VOC containing materials are added, maintain semi-annual records for all coating consisting of (a) coating type, (b) VOC content as supplied in grams per liter (g/l) of materials for low-solids coatings, (c) VOC content as supplied in g/l of coating, less water and exempt solvent, for other coatings.

For architectural applications where thinners, reducers, or other VOC containing materials are added, maintain daily records for each coating consisting of (a) coating type, (b) VOC content as applied in grams per liter (g/l) of materials used for low-solids coatings, (c) VOC content as applied in g/l of coating, less water and exempt solvent, for other coatings.

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : E107]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.2 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the filter

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D21, D22, D24, C96, D165]

K67.3 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the water wash

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D20]

K67.4 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

date of operation, elapsed time in hours, and reason for operation

[RULE 1110.2, 6-3-2005; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D115, D116, D119, D124, D125, D126, D127, D128, D129, D131, D133, D134, D146, D149, D159, D162, D163, D164, D169, D172, D173]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.5 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Purchase records of abrasive used or daily records of abrasives used and evidence of ARB certification

If abrasives are re-used, records to demonstrate that such abrasives are tested with CARB Method 371-A

Daily records of the description of items blasted to demonstrate compliance

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : D44]

K67.6 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

All maintenance, monthly and annual gasoline dispensed records, shall be prepared, shall be retained for five years, and shall be kept within the mobile fueler and made available to District representatives upon request.

All daily inspection records shall be completed immediately after the daily inspection.

[RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1303(b)(2)-Offset, 10-20-2000; RULE 461, 3-7-2008]

[Devices subject to this condition : D147]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.8 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The operator shall keep records in accordance with the requirements of rule 109 (record keeping for volatile organic compound emissions). Such records shall be retained for a period of three years and shall be made available to any district representative upon request.

Within 14 calendar days after the end of each month, the operator shall total and record VOC emissions for the month from all permitted equipment covered by the monthly limit. The record shall include any procedures used to account for control device efficiencies and/or waste disposal. It shall be signed and certified for accuracy by the highest ranking individual responsible for operation of equipment subject to the permit.

The operator shall maintain a single list which includes only the name and address of each person from whom the facility acquired VOC-containing material regulated by the district that was used or stored at the facility during the preceding 12 months.

The operator shall retain all purchase invoices for all VOC-containing material used or stored at the facility, and all waste manifest for all waste VOC containing material removed from the facility, for 36 months.

[RULE 109, 5-2-2003; RULE 1303(b)(2)-Offset, 5-10-1996]

[Devices subject to this condition : D165]

K67.10 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

the name of the person performing the inspection and/or maintenance of the baghouse

the date, time and results of the inspection

the date, time and description of any maintenance or repairs resulting from the inspection

[RULE 3004(a)(4)-Periodic Monitoring, 12-12-1997]

[Devices subject to this condition : C158]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.11 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

copy of MSDS shall be kept for the abrasive material used in this equipment

[RULE 1401, 12-7-1990]

[Devices subject to this condition : D156, D170]

K67.12 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

MSDS for the diesel fuel used in this equipment

[RULE 1303(a)(1)-BACT, 5-10-1996]

[Devices subject to this condition : D172]

K67.13 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The log shall list the date of operation, the timer reading in hours at the beginning and end of operation, and the reason for operation. The total hours of operation (include hours for manual and automatic operation) shall be recorded sometime during the first 15 days of January of each year.

[RULE 1110.2, 6-3-2005; RULE 1303(b)(2)-Offset, 5-10-1996; RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 10-15-1993; RULE 2005, 4-9-1999]

[Devices subject to this condition : D174]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.14 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

An engine operating log shall be kept and maintained on file to record when this engine is started manually. The log shall list the date of operation, the timer reading in hours at the beginning and end of operation, and the reason for operation for a minimum of five calendar years prior to the current year and made available to District personnel upon request. The total hours of operation (include hours for manual and automatic operation) shall be recorded sometime during the first 15 days of January

[RULE 1110.2, 6-3-2005; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996; RULE 2005, 4-20-2001**]

[Devices subject to this condition : D175, D176, D178, D182, D259, D276]

K67.15 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

The hours of operation per year.

[**RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1401, 12-7-1990]

[Devices subject to this condition : D177]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.16 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

An engine operating log shall be maintained which on a monthly basis shall include manual and automatic operation and shall list all engine operations in each of the following areas:

EMERGENCY USE HOURS OF OPERATION.

MAINTENANCE AND TESTING HOURS.

OTHER OPERATING HOURS (DESCRIBE THE REASON FOR OPERATION).

In addition, each time the engine is started manually, the log shall include the date of operation and the timer reading in hours at the beginning and end of operation. The log shall be kept for a minimum of three calendar years prior to the current year and made available to District personnel upon request. The total hours of operation for the previous calendar year shall be recorded sometime during the first 15 days of January of each year.

[RULE 1110.2, 6-3-2005; **RULE 1303(b)(2)-Offset, 5-10-1996**; RULE 1303(b)(2)-Offset, 12-6-2002; **RULE 1304(a)-Modeling and Offset Exemption, 6-14-1996**; RULE 1470, 6-1-2007; **RULE 2005, 4-20-2001**]

[Devices subject to this condition : D1, D2, D4, D7, D8, D12, D15, D95, D99, D153, D160, D168, D179, D180, D181, D183, D223]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.19 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

IN ACCORDANCE WITH RULE 461(j), THE OWNER/OPERATOR SHALL ADHERE TO THE FOLLOWING TASK COMPLETEION DATES AS SUBMITTED ON FORM 461-CP:

COMPLETE PERMIT APPLICATION PACKAGES TO ALL APPLICABLE GOVERNMENT AGENCIES NO LATER THAN 8/15/08

PURCHASE ORDER FOR CARB CERTIFIED PHASE II EVR SYSTEM NO LATER THAN 8/30/08

SIGN CONTRACT FOR INSTALLATION OF CARB CERTIFIED PHASE II EVER SYSTEM NO LATER THAN 8/11/2008

SIGN CONTRACT FOR TESTING OF CARB CERTIFIED PHASE II EVR SYSTEM NO LATER THAN 8/11/2008

START DATE OF EQUIPMENT INSTALLATION NO LATER THAN 11/15/2008

START DATE OF TESTING PHASE II EVR SYSTEM NO LATER THAN 12/30/2008

[RULE 461, 3-7-2008]

[Devices subject to this condition : D90]

K67.20 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

ALL RECORDS AND TEST RESULTS THAT ARE REQUIRED TO BE MAINTAINED BY RULE 461 SHALL BE KEPT ON SITE FOR FIVE YEARS AND MADE AVAILABLE TO DISTRICT REPRESENTATIVES UPON REQUEST.

[RULE 461, 3-7-2008]

[Devices subject to this condition : D36, D40, D88]

FACILITY PERMIT TO OPERATE DISNEYLAND RESORT

SECTION D: FACILITY DESCRIPTION AND EQUIPMENT SPECIFIC CONDITIONS

The operator shall comply with the terms and conditions set forth below:

K67.22 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Operating time records as required per conditons C1.23 and C1.24.

The records shall be kept for at least five years and made available to District personnel upon request

[**RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1303(b)(2)-Offset, 12-6-2002**]

[Devices subject to this condition : D266, D267, D268, D269, D270, D271, D272, D273, D274, D275]

K67.23 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Operating time records as required per conditons C1.16 and C1.26

The records shall be kept for at least five years and made available to District personnel upon request

[**RULE 1303(a)(1)-BACT, 5-10-1996**; **RULE 1303(a)(1)-BACT, 12-6-2002**; **RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1303(b)(2)-Offset, 12-6-2002**; **RULE 1401, 3-4-2005**]

[Devices subject to this condition : D284, D285, D286, D287, D288]

K67.24 The operator shall keep records, in a manner approved by the District, for the following parameter(s) or item(s):

Operating time records as required per conditons C1.14, C1.16 and C1.18

The records shall be kept for at least five years and made available to District personnel upon request

[**RULE 1303(a)(1)-BACT, 5-10-1996**; **RULE 1303(a)(1)-BACT, 12-6-2002**; **RULE 1303(b)(2)-Offset, 5-10-1996**; **RULE 1303(b)(2)-Offset, 12-6-2002**; **RULE 1401, 3-4-2005**]

[Devices subject to this condition : D224, D225, D226, D228, D229, D230, D231, D232, D233, D234, D235, D236, D237, D238, D239, D240, D241, D242, D243, D244, D246, D248, D249, D250, D252, D253, D255, D256, D257, D258, D262, D263, D264, D265]